



Specifications Ledvance LED  
Downlight Surface IP65 Aluminium  
Black 30W 3300lm 60D - 840 Cool  
White | IP65

[View Product](#)

General Information

|                          |                                         |
|--------------------------|-----------------------------------------|
| SKU                      | 247064                                  |
| EAN                      | 4058075769199                           |
| Brand                    | Ledvance                                |
| Manufacturer Name        | DL SURFACE DN 160 P 30W 840 60D IP65 BK |
| Any Lamp all-in warranty | 5 Years                                 |
| Average Lifetime (h)     | 100000                                  |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Tiltable                    | No              |
| Technology                  | LED Integrated  |
| Wattage                     | 30              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Including bulb              | Yes             |
| Beam Angle (degree)         | 60              |

|                          |                                |
|--------------------------|--------------------------------|
| Luminous Flux (Lumen)    | 3300                           |
| Luminous Efficacy (lm/W) | 110                            |
| Power factor             | >0.90                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | PC (Polycarbonate)             |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                             |
|------------------------|-----------------------------|
| Mounting Method        | Surface                     |
| Cut out (mm)           | 160                         |
| IP-rating              | IP65                        |
| Impact Protection (IK) | IK06 - 1 joule              |
| Operating Temperature  | -20 to +40                  |
| Housing                | Aluminium                   |
| Colour of the Fixture  | Black                       |
| Colour of material     | Black                       |
| Fixture Connection     | Terminal, 3-Pole (L, N, PE) |
| Series                 | DOWNLIGHT SURFACE IP65      |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 110 |
| Diameter (mm) | 160 |

## Why Any-lamp?

## Sensor Information

 Order from the **largest lighting specialist** in Europe
  **Customised** quotation

Type of sensor

No Sensor



Up to **7 years warranty**



**Easy** return process